

CUSTOM introduces on point of sale market the new KUBE, very high speed thermal printer, up to 220mm/sec, quiet and with high performance. KUBE represents a revolutionary printing solution for retail and hospitality market. Reduced dimensions and winning design (many available colours), make KUBE easy to place inside point of sale where space need is priority. KUBE can be vertical or horizontal mounted allowing to optimize working space and making it tidy thanks to hidden link cables. Paper roll high capacity, 90mm diameter, allows to increase printing autonomy. KUBE is able to print on 80mm or 82.5mm paper width. The printer is completed with drivers (Window and Linux) and utility for logo and character creation and updating. KUBE is available with serial RS232, USB, parallel and Ethernet interface and with cash drawer driver. KUBE is equipped with buzzer for sound signals, also polyphonics. It is possible to customize different melodies linked to special events (receipt issue, last ticket, etc..).



Available



LCD Customer Displays



Keyboards



PC Touch Terminal



Access Point

KUBE



- Very Fast and Quiet
- Compact Design
- 80/82.5mm Paper Width
- Robust and Reliable
- Large Paper Roll

| | Kube |
|--------------------------------|---|
| Printing method | Thermal line printing |
| Resolution | 203dpi (8dots/mm) |
| Printing speed (mm/sec) | High Quality 140, Normal 180, High Speed 220 |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858 (euro) |
| Type styles | Normal, 1x to 8x height and width, reverse, underscored, italic, bold |
| Printing direction | Straight, 90, 180, 270 |
| Paper width | 80mm/ 82.5mm |
| Paper thickness | from 65 to 100µm |
| Roll dimension | Max 90 mm |
| Emulation | CUSTOM/POS |
| Interface | Serial 25pin / USB Serial 9 pin / CX MB / CX STD |
| Data buffer | 4 KB |
| Flash memory | 384 KB |
| Graphic memory | 2 logos of 608 x 862 dots |
| Drivers | Win 2K, XP; Linux |
| Power consumption | 1,5 A* |
| Power supply | 24 Vdc +/- 10% (external power supply) |
| DKD function | 1 driver or customer display direct connection |
| MTBF | 360.000 hours** |
| Safety | EN60950 2001 |
| Marks: | CE, cUL, RoHS Compliant |
| Dimensions (WxDxH) | 140x208x152 mm |
| Weight | 2 Kg |



Splash Proof: water resist protection