



X KUBE manager full support CD-ROM includes logo and font editors, full drivers for Win2K/XP/2K3, status monitor and upgrade software and MidiToPrint application in order to transfer MIDI format sound into the printer, all together with logo and midi samples.



Access Point



120W optional power supply (> 250mm/sec printing speed)

X KUBE is a POS printer with enhanced quality and long life head and very high printing speed 250mm/sec. Paper loading is easy and fast thanks to the innovative system patented by CUSTOM. Moreover the paper roll high capacity, 90mm diameter, allows to increase printing autonomy. It prints on 80/82.5mm thermal paper width and it is available with serial, parallel, USB, Ethernet and Wi-Fi interfaces. Ethernet model is equipped with an internal printing server, friendly web window pages allow you to monitor printer status, to set both printer working parameters and network configuration. You can configure the email service to make maintenance and diagnostic operations easier.

X KUBE Ethernet becomes an ideal solution as wireless printer (standard 802.11b) thanks to the WIFI ADAPTER (or Ethernet Bridge), a device that can be connected directly to the X KUBE through the special cable that is included, without feeding necessity. To complete the WI-FI solutions range, it is available the ACCESS POINT that can be connected to the printer as the ADAPTER.

	X Kube
Printing method	Thermal line printing
Resolution	203dpi (8 dots/mm) / high quality and long life head
Printing speed (mm/sec)*	High Quality 120, Normal 180, High Speed 250 *
Character set	PC437, PC850, PC860, PC863, PC865, PC858 (euro);chinese fonts available (BIG5, GB2312)
Type styles	Normal, 1x to 8x height and width, reverse, underscored, italic, bold
Printing direction	Straight, 90, 180, 270
Paper width	80mm/82.5mm
Paper thickness	from 65 to 100µm
Roll dimension	Ø 90mm
Emulation	CUSTOM / POS
Interface	Serial 25pin / USB-Serial 9pin / CX MB / CX STD/ Ethernet / Wi-Fi
Data buffer	4 KB
Flash memory	384 KB
Graphic memory	2 logos of 608 x 862 dots (CUSTOM mode); multiple logos setting into NV memory (max 128Kb)
Drivers	Win 2K, XP; Linux, OPOS, JavaPOS
Power consumption	1.7 A**
Power supply	24 Vdc +/- 10% (external power supply)
DKD function	1 driver or customer display direct connection
MTBF	360.000 hours***
Safet	EN60950 2001
Marks	CE, cUL, RoHS compliant
Dimensions (WxDxH)	140x208x152 mm
Weight	2 Kg



* 250mm/sec printing speed with 80-90W power supply instead of the standard one (120W)

**50% printing rate
*** electronic board

- Enhanced Quality & Long Life Head
- Very Fast, 250 mm/sec
- 80/82.5mm Paper Width & Large Paper Roll
- Ethernet / Wi-Fi
- Full Support CD-ROM

