

## K80 - TORNADO PRINTER

80mm ticket / receipt printer

- 200dpi best printing quality
- Paper width from 76 to 80mm
- Paper roll (diameter 180mm on board)
- RS232 and USB interface
- 1D/ 2D barcodes printing capability (QR CODE)
- International fonts on board: any language available
- Highly reliable cutter
- Sensors: Head temperature, paper presence, near paper end, black mark 6 position, ticket out



## CHARACTERISTICS

### Ideal solution for ATM's VTM's & Self Service Kiosk

- Ultra-compact
- Heavy-duty alluminium printing engine
- Anti-jamming system
- Anti-instrusion shutter
- Anti-splash paper exit
- On/off switch



**PrinterSet SOFTWARE** : to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.

- CustomPowerTool

## AVAILABLE VERSIONS:

- K80 - TORNADO PRINTER: With output paper mouth, anti intrusion shutter and ticket sensor, low paper level sensor for roll up to 180mm
- K80 - PRINTING KIT: kit including printer mechanism, cutter & board, ideal for queue management

---

## ACCESSORIES

- Near paper end sensor for paper roll exceeding 180mm

## What is in the box:

- Device, locking ring
-

**TECHNICAL SHEET**


<b>Printing Method</b>	Thermal, fixed head
Number of dots	8 dot/mm
Resolution	203 dpi
Printing (mm/sec)	150 mm/s
Character set	54 character code tables Extended chinese GB18030-2000, Korean PC949
Supported Barcode	UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
Printing Format	Height/Width from 1 to 8, bold, reverse, underlined, italic
Printing Direction	Normal, 90°, 180°, 270°
Paper width	76, 80 ± 0,5 mm
Paper weight	from 55 g/m <sup>2</sup> to 80 g/m <sup>2</sup>
Paper thickness	from 63 $\mu$ m to 88 $\mu$ m
Printing width	from 52 to 80mm
Roll Dimension	max 180 mm
Sensors	Head temperature, paper presence, near paper end, black mark, ticket out
Emulation	CUSTOM/POS
Interfaces	USB + RS232 Serial
Data Buffer	8 Kbytes
Flash Memory	768 Kbytes internal, 4 Mbytes external
RAM Memory	128 Kbytes
Graphic Memory	1 logo (640x409 dots)
Drivers	Windows XP VISTA (32/64bit) Windows 7 (32/64bit) Windows 8 (32/64bit) Windows 8.1 (32/64bit) Linux (32/64bit)
Power supply	24 Vdc ±10% (optional external power supply)
Medium consumption	0.8 A (12,5% dots on)
MTBF	165 245 hours (electronic board)
Head Life	100 Km
MCBF	1.000.000 cut
Operating temperature	from 0°C to +50°C
Dimensions	258(L) x 103.5(H) x 135(W) mm
Weight	1250 g

**MODELS**



## **915LC011100300**

PRINTER K80 USB RS232  
SHUT+NOTCH+MOUTH



## **976LC010000001**

KIT MECHANISM + CUTTER +  
BOARD K80

---

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE:  
TI80WI0

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 16 April 2021