



## KPM216HIII ETH

### A4 document printer

- New latest generation **processor**
- New printing head with higher printing quality
- Speed > of 200mm/sec
- Illuminated paper bezel (standard equipment)
- Easy switch from horizontal to vertical setting
- Retracting, roll holding or fan fold in vertical position:the printer has a thickness of only 8cm!
- RS232+USB+Ethernet on board: 3 communication interfaces (standard equipment)
- Updates from remote thanks to Ethernet interface
- All international fonts on board
- 1D and 2D printing
- PrinterSet software : a tool for a complete, easy and quick management of your printer
- CPT software: CustomPowerTool for the personalization of your tickets/receipts
- Dot-saving function



## CHARACTERISTICS

- High print quality (300 DPI )
- Full featured loop presenter which avoids paper jams clearing the paper outlet through retracting the uncollected printout or through retracting it inside the kiosk for protecting the privacy of the user
- Adjustable paper-infeed
- Dot Damage Prevention: this function prevents the dots subject to stress caused by special printouts, like graphics and tables, from wearing out
- 100% hardware compatibility with previous Ethernet version

## APPLICATIONS:

- Form and document kiosks
- Banking machines
- Insurance self service
- Information kiosks
- Multimedia and Internet kiosks
- Human resource kiosks
- Boarding passes
- E-ticketing

## SOFTWARE:



**PrinterSet SOFTWARE :** to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.

- Automatic e-mail sending for service purposes
- Logo and font remote update
- Drivers available in the printer flash disk
- Dll status monitor
- Auto-installing drivers for WinXP, Vista, 7, 8, 8.1, 10 (32-64 bit support)
- Linux Drivers (C.U.P.S.) 32/64 bit compatible
- EthLocator SW to search for printers connected to the network and configure their parameters
- CPT software: CustomPowerTool for the personalization of your tickets/receipts

## AVAILABLE VERSIONS:

- Serial+USB+Ethernet 200 DPI 24V
- Serial+USB+Ethernet 300 DPI 24V

## TECHNICAL SHEET

	200 DPI model	300 DPI model
Printing Method	Thermal with fixed head	
Number of dots	8 dots/mm	12 dots/mm
Resolution	203 dpi	300 dpi
Printing (mm/sec)	200 mm/sec	
Character set	PC437, PC850, PC860, PC863, PC865, International	
Supported Barcode	1D and 2D	
Printing Format	Normal, height and width from 1x to 8x, reverse, underlined, script, bold	
Printing Direction	Straight, 90°, 180°, 270°	
Paper width	210 mm / 216 mm (A4" - US Letter)	
Paper weight	from 58 to 78 g/m <sup>2</sup>	
Paper thickness	from 63 to 85 µm	
Roll Dimension	Ø 180mm max	
Emulation	CUSTOM/POS	
Interfaces	RS232 + USB + Ethernet	
Data Buffer	19 KB	
Flash Memory	2MB internal flash and 8MB external SPI flash	
RAM Memory	128Kbytes	
Graphic Memory	5 logos with 1600 x 327 dots	5 logos with 2368 x 327 dots
Drivers	WinXP, Vista, 7, 8, 8.1, 10; Linux; Android	
Software Tools	PrinterSet, CustomPowerTool, DLL for developers, EthLocator	
Power supply	24 Vdc ± 10%	
Medium consumption	2.5 A (12,5% dots turned on)	
Head Life	100Km / 100M pulses	
MCBF	300,000 cuts	
Operating temperature	0°C + 50°C	
Dimensions	270 x 190 x 90 mm	
Weight	4.8 Kg	

## MODELS



**915AS050200700**  
 PRINTER KPM216HIII ETH USB  
 RS232 ESP 300



**915AS050100700**  
 PRINTER KPM216HIII ETH USB  
 RS232 ESP

---

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 05 December 2019