



TG1260HIII

60mm ticket / receipt printer

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 60 to 80 µm
- Printing > 60 mm/sec
- RS232 and USB interfaces
- It prints 1D and 2D barcodes (QRCODE)
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: head temperature, paper presence, anti paper jamming, ticket collection, paper end and near paper end

CHARACTERISTICS

- Zero power consumption in stand by mode
- Patented Anti Jamming System
- Suitable for tough environments, down to -20°C up to +70°C
- Illuminated paper bezel
- Multi-position paper roll
- Large paper roll: Ø 100 mm
- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality

APPLICATIONS:

- Self-service kiosks
- Banking machines
- Gaming machines
- Parking meters
- Queue management systems
- Vending machines


SOFTWARE:

- Remote status monitor
 - PrinterSet
 - CustomPowerTool
-

TECHNICAL SHEET

| | |
|------------------------|--|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Columns | 32 - 42 - 56 |
| Resolution | 203 DPI |
| Printing (mm/sec) | 60 mm/sec |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312 |
| Printing Format | Normal, height and width from 1 to 4, bold, negative, underlined, script, italic |
| Printing Direction | Straight, 180° |
| Paper width | 60 mm |
| Paper weight | from 55 to 70 g/m ² |
| Paper thickness | from 60 to 80 µm |
| Roll Dimension | 100 mm |
| Sensors | Head temperature, paper jamming, paper presence, notch presence, optional: almost external paper end |
| Emulation | Custom/POS, TGH |
| Interfaces | RS232 + USB |
| Data Buffer | 2 kB |
| Flash Memory | 4 MB |
| Graphic Memory | 2 logos of 448x584 dots |
| Drivers | Windows Virtual COM Linux |
| Software Tools | Status Monitor, PrinterSet, CustomPowerTool |
| Power supply | 12V +/- 10% |
| Medium consumption | 0.66A (12.5% dots turned on) |
| MTBF | 420,000 hours (electronic board) |
| Head Life | 50Km/100M pulses |
| Operating temperature | -20°C + 70°C |
| Dimensions | 100x120(h)x93 mm (with front) - 118x80(h)x114 mm (with automatic cutter) |
| Weight | 0.6 Kg |

MODELS



915CD080100300

PRINTER TG1260HIII USB CUTTER
LED OUT

CUSTOM S.P.A. - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 06 May 2021