

TG2460HIII TEAR OFF

Printer for filling stations

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 60 to 80 µm
- Printing > 140 mm/sec
- RS232 and USB interfaces
- Barcodes: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- Characters: European, International, Thai, Portuguese, Nordic, Arabic, Chinese and Russian
- Sensors: head temperature, paper presence, anti paper jamming, ticket collection, paper end and near paper end

CHARACTERISTICS

- 60 mm ticket dispenser with patented tear off system (without auto-cutter) and chromed bezel resistant to hydrocarbons, which makes the printer suitable for use at fuel stations.
- Special paper auto-loading system
- Possibility to fit the roll holder arm to the right or to the left
- Suitable for tough environments, from -20°C up to +70°C

EXCLUSIVE FEATURES:

- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality


SOFTWARE:

- Auto-installing driver for WinXP/Vista/7(+64bit support)
- Windows CE 3.0/5.0 Drivers (PLC)
- Linux Driver (C.U.P.S.) 32/64 bit compatible
- Remote status monitor
- PrinterSet
- CustomPowerTool

TECHNICAL SHEET

Printing Method	Thermal with fixed head
Number of dots	8 dots/mm
Columns	32 - 42 - 56
Resolution	203 DPI
Printing (mm/sec)	140mm/sec
Character set	PC437, PC850, PC860, PC863, PC865, PC858, PC866, GB2312
Printing Format	Normal, height and width from 1 to 4, bold, negative, underlined, script, italic
Printing Direction	Straight, 180°
Paper width	60 mm
Paper weight	from 55 to 70 g/m ²
Paper thickness	from 60 to 80 µm
Roll Dimension	100 mm
Sensors	Head temperature, paper jamming, paper presence, notch presence, optional: almost external paper end
Emulation	Custom/POS, TGH
Interfaces	RS232 + USB
Data Buffer	2 kB
Flash Memory	1 MB
Graphic Memory	2 logos of 448x584 dots
Drivers	XP / Vista / 7(+64 bit support) / Windows CE 3.0/5.0 / Linux 32/64 bit compatible
Software Tools	Status Monitor, PrinterSet, CustomPowerTool
Power supply	24V +/- 10%
Medium consumption	0.62A (12.5% dots turned on)
MTBF	420,000 hours (electronic board)
Head Life	50Km/100M pulses
Operating temperature	-20°C + 70°C
Dimensions	100x120(h)x93 mm (with front) - 118x80(h)x114 mm (with automatic cutter)
Weight	0.6 Kg

MODELS



915CG030100300

PRINTER TG2460HIII USB TEAR OFF
CROMED BEZEL

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: T180W10

The technical data on this website are not binding and may be changed without advanced notice.
Last update: 05 December 2019