



TK202III

Ticket printer

TK202III is a very fast ticket printer, featuring a printing speed > 200mm/s. Different ticket widths, from 20 to 82.5 mm, easily adjustable by the user. Ticket weight (in grams): from 80 to 255 g/m². 1D and 2D barcode printing.



CHARACTERISTICS

- Ticket printer for heavy workloads
- Printing speed up to 200 mm/s
- Ticket width: from 20 to 82.5 mm
- Ticket weight (in grams): from 70 to 255 g/m²
- Improved print head quality for crisp printouts
- Fan-fold / paper roll holder
- Embedded display on 2 lines

FOCUS ON

- 1D and 2D barcode printing: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, QRCODE
- RS232 + USB interface
- Sensors: fully adjustable lower and upper optical sensor, to suit any ticket width and to detect black marks/gaps
- The tear-off function is the ideal solution to reduce costs, the cutter does not wear even with labels
- Graphics: dynamic logo (graphic memory max 2MB)
- Characters: True Font character support, any language available

ACCESSORIES

What is in the box:

- Device, ruler, AC adapter, short guide, reducer for paper width <40mm, serial cable, USB cable, 220V power cable

TECHNICAL SHEET

| | |
|------------------------|--|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Resolution | 203 DPI |
| Printing (mm/sec) | >200 mm/sec |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858 |
| Printing Format | Height and width from 1x to 8x, reverse, underlined, italic, bold |
| Printing Direction | Straight, 90°, 180°, 270° |
| Paper width | From 20mm to 82.5mm (2mm step) |
| Paper weight | from 70 to 255 g/m ² |
| Emulation | CUSTOM/POS - SVELTA |
| Interfaces | RS232 / USB |
| Data Buffer | 64 KB |
| Flash Memory | 16 MB |
| Graphic Memory | Dynamic logo management (graphic memory max 2MB) |
| Drivers | Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); OPOS; Android™; iOS |
| Software Tools | PrinterSet, CustomPowerTool, Status Monitor |
| Power supply | 24 Vac ± 10% |
| Medium consumption | 0.8A (12,5% dots turned on) |
| Head Life | 100Km /100M pulses |
| Dimensions | 252.1 (L) x 192.6 (H) x 216 (W) mm |
| Weight | 4 Kg |

MODELS



911BD050100313

PRINTER TK202III USB RS232

Via I. Newton, 4 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 09 June 2026