



## TL60III

### 60mm ticket / receipt printer

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 63 to 85  $\mu$ m
- Printing > 140 mm/sec
- RS232 and USB interfaces
- Barcodes: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: paper presence and head opening



## CHARACTERISTICS

- Extremely compact: just 77mm high
- Suitable for tough environments, down to -20°C up to +70°C
- Multi-position paper roll holder: lower, top or rear position
- Paper roll diameter up to 80 mm
- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality

## APPLICATIONS

- Self-service kiosks
  - Banking machines
  - Gaming machines
  - Parking pay terminals
  - Queue management systems
  - Vending machines
- 

## ACCESSORIES

### What is in the box:

- Device, power supply cable, fixing screws for paper roll holder, paper roll holder
-

## TECHNICAL SHEET

|                        |   |
|------------------------|---|
| <b>Printing Method</b> | Thermal with fixed head   |
| Number of dots         | 8 dots/mm   |
| Columns                | 24 - 32 - 44  |
| Resolution             | 203 DPI   |
| Printing (mm/sec)      | 140mm/sec   |
| Character set          | PC437, PC850, PC860, PC863, PC865, PC858, PC866, VISCII (Option 0104: PC437, PC850, PC860, PC863, PC865, PC858, GB2312)                             |
| Printing Format        | Normal, height and width from 1 to 4, bold, negative, underlined, script  |
| Printing Direction     | Straight, 180°  |
| Paper width            | 60 mm   |
| Paper weight           | from 55 to 80 g/m <sup>2</sup>  |
| Paper thickness        | from 63 to 85 $\mu$ m   |
| Roll Dimension         | max 80mm  |
| Sensors                | Head temperature, paper presence  |
| Emulation              | Custom/POS, TGH   |
| Interfaces             | RS232 + USB   |
| Data Buffer            | 2 kB  |
| Flash Memory           | 1 MB  |
| Graphic Memory         | 2 logos 448x584 dot   |
| Drivers                | Windows® (32/64 bit) – only on request WHQL and silent installation;<br>Linux (32/64 bit);<br>Virtual COM (Linux or Windows 32/64 bit);<br>Android™ |
| Software Tools         | Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API   |
| Power supply           | 24V +/- 10%   |
| Medium consumption     | 0.65A (12,5% dots on)   |
| MTBF                   | 172.000 hours (electronic board )   |
| Head Life              | 50Km/100M pulses  |
| Cutter                 | TL60III Partial / Total cut<br>TL60III EJ Total cut   |
| Operating temperature  | -20°C + 70°C  |
| Dimensions             | 130(L)x105(W)x77(H)mm   |
| Weight                 | 0.800 Kg  |

## MODELS



**915CJ040100300**

PRINTER TL60III USB RS232



**915CJ040200300**

PRINTER TL60III USB RS232  
EJECTOR

---

Via I. Newton, 4 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 07 April 2026