



MT15

Monitor Touch with backlit LED panel

Monitor touch with backlit LED panel, 1000 nits high brightness, MT15 offers an high contrast quality and a solution that can be read with solar light. The capacitive touch screen supplies an application of multi-touch inputs. The touch screen has a lunette sealing with IP65 protection on the front side to avoid the entrance of liquids and dust. The product is ready for VESA vertical mounting, is compatible with HID for an easy integration with thin client. Worldwide certifications such as: TUV, CE, UL, CUL, FCC-B, RoHS and IPX1.



CHARACTERISTICS

- **Display:** 15" diagonal TFT Active Matrix Panel
- **Colors:** 16.2M (6 bits + FRC)
- **Resolution:** 1024 X 768 (Max.)
- **Brightness:** With Touch Capacitive: 225 nits (typical) / 900 nits (typical)
- **Touch screen:** Projected Capacitive: 10 dot
- **Touch Interface:** USB (type B)
- **Power Supply:** AC 100 ~ 240 (V)
- **Dimension:** 350.8 (W) X 306.5 (H) X 202.0 (D) mm
- **Weight:** 4,5 Kg

FOCUS ON:

Energy consumption: Operating:20W (typ.) / Sleep: 3W / Off: 1W

Mounting option: Stand / 100 X 100 mm VESA Mount

Environmental features

Temperature - Operating 0 °C ~ +40 °C

Temperature - Storage -20 °C ~ +60 °C

Humidity - Operating 20% ~ 80% (Non condensing)

Humidity - Storage 10% ~ 90% (Non condensing)

Plug & Play

DDC 2B Compatible

Certifications

TVU, CE, UL, CUL, FCC-B, RoHS, IPX1

MODELS



932AD060100233

MONITOR TOUCH 15" MT15

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: TI80WIO

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 01 April 2020