



TL60III

60mm ticket / receipt printer

- Metal frame (galvanized/aluminium alloy)
- High print quality (200 DPI)
- Paper width: 60mm
- Paper thickness: from 63 to 85 μ m
- Printing > 140 mm/sec
- RS232 and USB interfaces
- Barcodes: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- Characters: European, International, Portuguese, Nordic, Arabic, Chinese and Russian
- Highly reliable cutter: over 1,000,000 cuts
- Sensors: paper presence and head opening



CHARACTERISTICS

- Extremely compact: just 77mm high
- Suitable for tough environments, down to -20°C up to +70°C
- Multi-position paper roll holder: lower, top or rear position
- Paper roll diameter up to 80 mm
- Metal structure that provides increased rigidity for the printing mechanism and facilitates motor heat dissipation, resulting in improved stability and reliability over time
- Improved distribution of the head-roller pressure, resulting in improved printing quality

APPLICATIONS

- Self-service kiosks
 - Banking machines
 - Gaming machines
 - Parking pay terminals
 - Queue management systems
 - Vending machines
-

ACCESSORIES

What is in the box:

- Device, power supply cable, fixing screws for paper roll holder, paper roll holder
-

TECHNICAL SHEET

| | |
|------------------------|---|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Columns | 24 - 32 - 44 |
| Resolution | 203 DPI |
| Printing (mm/sec) | 140mm/sec |
| Character set | PC437, PC850, PC860, PC863, PC865, PC858, PC866, VISCII (Option 0104: PC437, PC850, PC860, PC863, PC865, PC858, GB2312) |
| Printing Format | Normal, height and width from 1 to 4, bold, negative, underlined, script |
| Printing Direction | Straight, 180° |
| Paper width | 60 mm |
| Paper weight | from 55 to 80 g/m ² |
| Paper thickness | from 63 to 85 μ m |
| Roll Dimension | max 80mm |
| Sensors | Head temperature, paper presence |
| Emulation | Custom/POS, TGH |
| Interfaces | RS232 + USB |
| Data Buffer | 2 kB |
| Flash Memory | 1 MB |
| Graphic Memory | 2 logos 448x584 dot |
| Drivers | Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); Android™ |
| Software Tools | Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API |
| Power supply | 24V +/- 10% |
| Medium consumption | 0.65A (12,5% dots on) |
| MTBF | 172.000 hours (electronic board) |
| Head Life | 50Km/100M pulses |
| Cutter | TL60III Partial / Total cut TL60III EJ Total cut |
| Operating temperature | -20°C + 70°C |
| Dimensions | 130(L)x105(W)x77(H)mm |
| Weight | 0.800 Kg |

MODELS



915CJ040100300

PRINTER TL60III USB RS232



915CJ040200300

PRINTER TL60III USB RS232
EJECTOR

Via I. Newton, 4 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 08 May 2026