



TP6

All-in-One POS Terminal

With a sleek yet robust design, the TP6 is the perfect enterprise-grade POS solution. The TP6 features a 15" TruFlat projected capacitive touchscreen, a range of Intel CPUs, cable free accessories and a versatile dual hinge design.



CARACTERÍSTICAS

RESILIENT TOUCH DISPLAY

The TP6 features a 15" LCD screen with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy use.

VERSATILE PLATFORM

A dual hinge design allows for efficient shipping and almost unlimited tilt angles. Built-in VESA mounting extends the versatility of the platform to any wall mount installation.

FAN-LESS DESIGN

A fan-less design provides a sleek, clean look and silent operation. No vent openings mean better protection from dust and water reaching an IP54 ingress protection rating.

EFFICIENT HIGH PERFORMANCE CPUs

With support for Intel CPUs ranging from the efficient J1900 to the powerful Core i5, the TP6 is sure to fit any application

ACCESORIOS

- Card Reader (MSR)
- Biometric Reader
- 2-line Rear Display
- 10.1" Rear Display
- Attached Augusta Reader Bracket

What is in the box:

AIO POS Terminal, AC Power Adapter + Cord, RJ45 to DB9 Serial Cable

FICHA TÉCNICA

| MODEL | TP6D-F | TP6D-3 | TP6D-5 | TP6W-3 |
|----------------|---|---------------------|--|---------------------|
| Processor | Intel Celeron J1900 | Intel Core i3-6100U | Intel Core i5-6200U | Intel Core i3-6100U |
| Bezel | TruFlat Bezel | | | |
| Chip Set | Processor Integrated | | | |
| System Memory | 1 x DDR3L SO-DIMM 4GB - 8GB | | 1 x DDR3L SO-DIMM 8GB | |
| Hard Drive | 2.5" 64-500GB SSD or 2.5" 500GB HDD | | | |
| LCD Display | 15" (381mm) TFT LCD | | 18.5" (470mm) TFT LCD | |
| Resolution | 1024x768 | | 1920x1080 | |
| Touch | PCAP,10 Point Multi-Touch | | | |
| Brightness | 300 nits | | 350 nits | |
| Graphic Engine | Intel HD Graphics DX11 and OCL1.1 | | Intel HD Graphics DX12 and OCL4.2 | |
| TPM | N/A | | 2.0 | |
| Electrical | 65W/19V | | 90W/19V | |
| Supported OS | Win 7 Pro (x32/x64), POSReady 7(x32/x64), Win 10 IoT(x32/x64) | | Win 8.1 Embedded (x64),Win 8.1 Pro (x64),Win 10 IoT (x64),Win 10 Pro (x64) | |

PORTS

| | | | |
|-----|---|--|---|
| I/O | 4 x USB 2.0 / 1 x USB 3.0 3 x RJ45 with 0V/5V/12V power Serial 1 x RJ45 LAN Dual Band 802.11 a/b/g/n/ac 2.4GHz/5GHz 1 x RJ11 (12V/24V) Cash Drawer Port 1 x DB15 VGA | 2 x USB 2.0 Type A / 4 x USB 3.0 3 x RJ45 with 0V/5V/12V power Serial 1 x RJ45 LAN Dual Band 802.11 a/b/g/n/ac 2.4GHz/5GHz 1 x RJ11 (12V/24V) Cash Drawer Port 1 x DB15 VGA | 2 x USB 2.0 Type A / 4 x USB 3.0 3 x RJ45 with 0V/5V/12V power Serial 1 x RJ45 LAN 1 x RJ11 (12V/24V) Cash Drawer Port 1 x DB15 VGA |
|-----|---|--|---|

PHYSICAL

| | | | | |
|-----------------------------|--------------------------------------|--|--------------------|--|
| Housing | Die Cast Aluminum | | | |
| Weight | 13.2 lbs | | 9.6 lbs | |
| Dimensions (w/base) (WxDxH) | 14.2" x 8" x 10.9" | | 18.1" x 8" x 11.4" | |
| Tilt | Dual Hinge | | | |
| Housing Color | Black | | | |
| Wall Mount | 100mm VESA (75mm or 100mm with base) | | | |

ENVIRONMENTAL

| | | | | |
|-----------------------|--------------------------------------|--|--|--|
| IP Rating | IP54 (Front) Splash Resistant Screen | | | |
| Operating Temperature | 32°F - 95°F (0°C - 35°C) | | | |
| Humidity | 20%- 80%RH non-condensing | | | |
| Certifications | FCCClass B, CE, LVD, NOM | | | |
| Viewing Angle | Horizontal: 140°, Vertical 130° | | | |
| Warranty | 3 years | | | |

MODELOS



935KY402Y00L33

15", Celeron J1900, 4GB, 120GB
SSD, Win 10 IoT x64



935KY400200L33

15", Core i3 6100U, 4GB, 120GB
SSD, No O/S



935KY401700L33

15", Core i3 6100U, 8GB, 500GB
SSD, Win 10 IoT x64



935KY402300L33

15", Core i5 6200U, 8GB, 500GB
SSD, Win 10 Pro x64

Via I. Newton, 4 - 43010 Fontevivo PR - N° IVA: IT02498250345 - TEL.: +39 0521 680111 - FAX: - CÓDIGO ÚNICO: 8RQN7AZ

Los datos técnicos de este sitio no son vinculantes y pueden modificarse sin aviso previo.

Última actualización: 24 abril 2026