



D4 102

Imprimante d'étiquettes

D4 102 est une imprimante 4" d'étiquettes de bureau compacte avec des dotations de niveau industriel et de hautes performances. Ports multiples de communication, touche multi-fonction et LED pour travailler aisément et montrer l'état d'erreur : ce ne sont que quelques-unes des caractéristiques qui font de cette imprimante un produit idéal pour des applications d'étiquetage.



FICHE TECHNIQUE

	D4 102	D4 102 ETH
Processor		32bit RISC processor
Programming languages		EPL
Printing Method		Direct thermal / Thermal transfer
Resolution		203 dpi
Print speed		5 ips
Max. Print Length		3810 mm
Print Width		104 mm
Sensors	Moveable reflective sensor (movable from the center to the left side)	Cover open sensor Ribbon sensor
RAM Memory		64 MB SDRAM
Flash Memory		128 MB
Control Panel		1 multi-functional keys 6 status LED lights
Media		Maximum label width: 110 mm Minimum label width: 15 mm Maximum roll diameter: 127 mm Core diameter: 25.4 mm Media thickness: 0.06mm to 0.2mm Media type: Continuous, die-cut, tag, fan-f black mark
Ribbon		OD: 39 mm Max length: 100 m Width: 25.4 mm to 110 mm ID:12.7mm Ribbon type: Wax, wax/resin, resin
Emulation Language		PEPL, PDPL, PZPL
Interfaces	USB port Ethernet port 10/100 Mbps (option)	USB port Ethernet port 10/100 Mbps on board
Supported 1D/2D Barcodes		Code39 standard or extended, Code39 with check digit, Code93, Code128 UCC, Code128 a modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN13, Interleaved 2 of 5, Interleaved 2 check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5, Code11 Data Matrix, MaxiCode, PDF417, QR code
Fonts		5 internal expandable bitmap fonts (alpha-numeric) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees 2 internal expandable bitmap fonts (numeric only)
Drivers		Windows® (32/64 bit) – only on request WHQL and silent installation
Image		PEPL: PCX, Direct binary graphic PDPL : PCX, BMP, HEX
Options		Peeler kit Guillotine Cutter Ethernet module
Power		Switching power adapter Input: 100 to 240 V, 1 .8 A, 50~60 Hz Output: 24 V, 2.5 A

D4 102

D4 102 ETH

Environment	Operation: 5 °C to 45°C Storage: -20 °C to 50 °C
Humidity	Operation: 10% to 90% non condensing Storage: 5% to 95% non condensing
Dimensions	263 mm (L) × 200 mm (W) × 188 mm (H)
Weight	2 kg

MODÈLES



911MK010100233

LABEL PRINTER D4 102 USB
BLACK



911MK010300J33

LABEL PRINTER D4 102 ETH USB
BLACK

Via I. Newton, 4 - 43010 Fontevivo PR - NUMÉRO DE TVA : IT02498250345 - TÉL : +39 0521 680111 - FAX : - CODE UNIVOQUE: 8RQN7AZ

Les données techniques de ce site ne sont pas contraignantes et peuvent être modifiées sans préavis.

Dernière mise à jour : 22 avril 2026