



# TP6

## All-in-One POS Terminal

With a sleek yet robust design, the TP6 is the perfect enterprise-grade POS solution. The TP6 features a 15" TruFlat projected capacitive touchscreen, a range of Intel CPUs, cable free accessories and a versatile dual hinge design.



## CARATTERISTICHE

### RESILIENT TOUCH DISPLAY

The TP6 features a 15" LCD screen with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy use.

### VERSATILE PLATFORM

A dual hinge design allows for efficient shipping and almost unlimited tilt angles. Built-in VESA mounting extends the versatility of the platform to any wall mount installation.

### FAN-LESS DESIGN

A fan-less design provides a sleek, clean look and silent operation. No vent openings mean better protection from dust and water reaching an IP54 ingress protection rating.

### EFFICIENT HIGH PERFORMANCE CPUs

With support for Intel CPUs ranging from the efficient J1900 to the powerful Core i5, the TP6 is sure to fit any application

---

## ACCESSORI

- Card Reader (MSR)
- Biometric Reader
- 2-line Rear Display
- 10.1" Rear Display
- Attached Augusta Reader Bracket

### What is in the box:

AIO POS Terminal, AC Power Adapter + Cord, RJ45 to DB9 Serial Cable

---

## SCHEMA TECNICA

| MODEL          | TP6D-F  | TP6D-3              | TP6D-5   | TP6W-3              |
|----------------|---|---------------------|--|---------------------|
| Processor      | Intel Celeron J1900   | Intel Core i3-6100U | Intel Core i5-6200U  | Intel Core i3-6100U |
| Bezel          | TruFlat Bezel   |                     |  |                     |
| Chip Set       | Processor Integrated  |                     |  |                     |
| System Memory  | 1 x DDR3L SO-DIMM 4GB - 8GB                                   |                     | 1 x DDR3L SO-DIMM 8GB  |                     |
| Hard Drive     | 2.5" 64-500GB SSD or 2.5" 500GB HDD                           |                     |  |                     |
| LCD Display    | 15" (381mm) TFT LCD   |                     | 18.5" (470mm) TFT LCD  |                     |
| Resolution     | 1024x768  |                     | 1920x1080  |                     |
| Touch          | PCAP,10 Point Multi-Touch                                     |                     |  |                     |
| Brightness     | 300 nits  |                     | 350 nits   |                     |
| Graphic Engine | Intel HD Graphics DX11 and OCL1.1                             |                     | Intel HD Graphics DX12 and OCL4.2  |                     |
| TPM            | N/A   |                     | 2.0  |                     |
| Electrical     | 65W/19V   |                     | 90W/19V  |                     |
| Supported OS   | Win 7 Pro (x32/x64), POSReady 7(x32/x64), Win 10 IoT(x32/x64) |                     | Win 8.1 Embedded (x64),Win 8.1 Pro (x64),Win 10 IoT (x64),Win 10 Pro (x64) |                     |

## PORTS

|     |   |  |   |
|-----|---|--|---|
| I/O | 4 x USB 2.0 / 1 x USB 3.0<br>3 x RJ45 with 0V/5V/12V power Serial<br>1 x RJ45 LAN<br>Dual Band 802.11 a/b/g/n/ac 2.4GHz/5GHz<br>1 x RJ11 (12V/24V) Cash Drawer Port<br>1 x DB15 VGA | 2 x USB 2.0 Type A / 4 x USB 3.0<br>3 x RJ45 with 0V/5V/12V power Serial<br>1 x RJ45 LAN<br>Dual Band 802.11 a/b/g/n/ac 2.4GHz/5GHz<br>1 x RJ11 (12V/24V) Cash Drawer Port<br>1 x DB15 VGA | 2 x USB 2.0 Type A / 4 x USB 3.0<br>3 x RJ45 with 0V/5V/12V power Serial<br>1 x RJ45 LAN<br>1 x RJ11 (12V/24V) Cash Drawer Port<br>1 x DB15 VGA |
|-----|---|--|---|

## PHYSICAL

|                             |                                      |  |                    |  |
|-----------------------------|--------------------------------------|--|--------------------|--|
| Housing                     | Die Cast Aluminum                    |  |                    |  |
| Weight                      | 13.2 lbs                             |  | 9.6 lbs            |  |
| Dimensions (w/base) (WxDxH) | 14.2" x 8" x 10.9"                   |  | 18.1" x 8" x 11.4" |  |
| Tilt                        | Dual Hinge                           |  |                    |  |
| Housing Color               | Black                                |  |                    |  |
| Wall Mount                  | 100mm VESA (75mm or 100mm with base) |  |                    |  |

## ENVIRONMENTAL

|                       |                                      |  |  |  |
|-----------------------|--------------------------------------|--|--|--|
| IP Rating             | IP54 (Front) Splash Resistant Screen |  |  |  |
| Operating Temperature | 32°F - 95°F (0°C - 35°C)             |  |  |  |
| Humidity              | 20%- 80%RH non-condensing            |  |  |  |
| Certifications        | FCCClass B, CE, LVD, NOM             |  |  |  |
| Viewing Angle         | Horizontal: 140°, Vertical 130°      |  |  |  |
| Warranty              | 3 years                              |  |  |  |

## MODELLI



### **935KY402Y00L33**

15", Celeron J1900, 4GB, 120GB  
SSD, Win 10 IoT x64



### **935KY400200L33**

15", Core i3 6100U, 4GB, 120GB  
SSD, No O/S



### **935KY401700L33**

15", Core i3 6100U, 8GB, 500GB  
SSD, Win 10 IoT x64



### **935KY402300L33**

15", Core i5 6200U, 8GB, 500GB  
SSD, Win 10 Pro x64

---

Via I. Newton, 4 - 43010 Fontevivo PR - P. IVA: IT02498250345 - TEL: +39 0521 680111 - FAX: - CODICE UNIVOCO: 8RQN7AZ

I dati tecnici presenti su questo sito non sono impegnativi e possono essere modificati senza preavviso.

Ultimo aggiornamento: 08 maggio 2026