



TG02H

Extremely compact and versatile ticket printer

Extremely compact and versatile ticket printer, for easy installation and panel mounting. TG02H is available with black plastic bezel.

- Best quality print quality (200 DPI)
- Paper width: 57mm
- Printing > 80 mm/sec
- Up to 70mm paper roll diameter
- RS232 + USB interfaces (serial TTL with welding)
- Highly reliable tear off system
- Sensors: head temperature, paper presence, near paper end, anti-jamming
- Power supply: 12V and 24V

CARACTERÍSTICAS

- 1D/ 2D (QR CODE) barcode printing feature
- International fonts on-board: any language available
- Patented anti-jamming system
- Outdoor applications: 20/+ 70°C operating temperature
- Low power consumption in stand-by mode
- Roll holder included

APPLICATIONS:

- Gaming machines
- Queue management systems
- Vending machines
- Self-service kiosks

SOFTWARE:



PrinterSet SOFTWARE : to update logos, edit characters, set operating parameters and update the printer firmware. It allows you to create a file including the different SW customizations and send them to the printer via the interface provided, for easy and fast setting.


AVAILABLE VERSIONS:

- Serial + USB 57mm 12-24V with plastic, black bezel
-

FICHA TÉCNICA

| | |
|------------------------|---|
| Printing Method | Thermal with fixed head |
| Number of dots | 8 dots/mm |
| Columns | Default 24; 32 and 42 possible columns with different fonts |
| Resolution | 203 DPI |
| Printing (mm/sec) | 80 mm/s (load 50 mm/s) |
| Character set | International (default), Chinese, Korean |
| Supported Barcode | 1D/ 2D QR CODE |
| Printing Format | Normal, height and width from 1 to 8, bold, negative, underlined, script |
| Printing Direction | Straight, 180° |
| Paper width | 57 mm |
| Paper weight | from 55 to 60 g/m ² |
| Printing width | 48 mm |
| Roll Dimension | Up to 70mm |
| Sensors | Head temperature, paper presence, near paper end, anti-jamming |
| Emulation | Escape Command compatibility |
| Interfaces | RS232 (TTL available), USB, AUX Gaming Optional |
| Data Buffer | 8 KB |
| Flash Memory | 4 MB |
| RAM Memory | 512 KB |
| Graphic Memory | 2 Logo: 384x682 dots |
| Drivers | Windows, Android, iOS, Linux |
| Software Tools | PrinterSet, CustomPowerTool |
| Power supply | 12 - 24 Vdc ± 10% |
| Medium consumption | 0.7 A (12Vdc) 0.4 A (24Vdc) |
| MTBF | 420,000 hours (electronic board) |
| Head Life | 50Km/100M pulses |
| Operating temperature | -20/+ 70°C |
| Dimensions | 129(L) x 120(H) x 100(W) mm (black bezel) 126.2(L) x 85.2(H) x 92(W) mm (illuminated bezel) |
| Weight | 0.33 kg without paper roll |

MODELOS



915HZ010300300

PRINTER TG02H USB RS232

CUSTOM SPA - Via Berettine, 2 - 43010 Fontevivo PR - P. IVA: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - CÓDIGO UNÍVOCO: T180W10

As informações técnicas neste site não são vinculadas e podem ser alteradas sem aviso prévio.

Última atualização: 01 abril 2020