



## TREK Monitor 15.6"

### 15.6" Touchscreen Monitor

With its sleek and minimalistic design, the **TREK 15.6" Monitor** fits wherever touchscreen functionality is required. **POS, Self-Service, KDS, Price Checker**, and more, TREK Monitor offers flexibility to install as either an operator touchscreen or an interactive customer facing display. Deploy countertop on the included stand or leverage the 75mm VESA pattern for pole and wall mounting. Purpose built for commercial environments, TREK Monitor features single USB-C cable convenience and rugged IP54 protection. And, as with all TREK products, you can easily add accessories to transform TREK Monitor for any use case.

To learn more about the entire TREK family of products, please [click here](#).



## CARACTERÍSTICAS

### 1. Simplicity

TREK Monitor simplifies connectivity via a single USB-C cable which provides touch, video signal and power. Alternatively, HDMI, USB-A and power connectors are also available to support legacy connections to POS systems, PCs and compute boxes.

### 2. Versatility

TREK Monitor supports all TREK micro USB accessories allowing for endless configurations to support a variety of use cases.

### 3. Flexibility

Whether placed on the counter via the included stand or mounted onto any 75 x 75 mm VESA pole or bracket, the TREK monitor can be positioned wherever needed to best serve the customer.

### 4. Durability

Retail-hardened and backed by Custom's warranty support, TREK Monitor is built to withstand the rigors of any environment.

## MARKETS

- Retail
- Hospitality
- Grocery
- C-Store
- Entertainment
- Gaming, Lottery and Betting

---

## ACESSÓRIOS

|                       |  |
|-----------------------|--|
| <b>938PW010100001</b> | Fingerprint Reader for Trek Terminal   |
| <b>938PW010100002</b> | 2D scanner for Trek Terminal           |
| <b>938PW010100003</b> | 3 Track MSR for Trek Terminal          |
| <b>938PW010100004</b> | NFC/RFID Reader for Trek Terminal      |
| <b>938PW010100005</b> | LED Light Bar for Trek Terminal        |
| <b>938PW010100006</b> | Camera/Microphone for Trek Terminal    |
| <b>938PW010100012</b> | iButton Reader for Trek Terminal       |
| <b>938PW010100007</b> | Trek series POS stand all screen sizes |

---

## FICHA TÉCNICA

|                              |  |
|------------------------------|--|
| <b>Touch Display</b>         | 15.6"  |
| <b>Resolution</b>            | 1920 x 1080  |
| <b>Aspect Ratio</b>          | 16:9   |
| <b>Touch Technology</b>      | True-Flat PCAP multi-touch   |
| <b>Touch Interface</b>       | USB  |
| <b>Brightness</b>            | LCD Panel: 300 NITS   PCAP Touch: 240 NITS   |
| <b>Viewing Angle</b>         | Horizontal: ±89° or 178° total / Vertical: ±89° or 178° total  |
| <b>USB Type-C</b>            | 1x USB 3.0 full-functioned (DP / PD 5 V / 2 A, 12 V / 1 A)   |
| <b>HDMI</b>                  | 1x   |
| <b>Micro USB</b>             | 3x   |
| <b>DC Jack</b>               | 1x 2 pin   |
| <b>Speaker</b>               | 1x 3 W   |
| <b>Auto Adjust Button</b>    | 1x   |
| <b>Power Button</b>          | 1x   |
| <b>Stand</b>                 | Included   |
| <b>VESA Mount</b>            | 75 x 75 mm   |
| <b>Accessory Options</b>     | 2D Scanner, Camera / Microphone, Fingerprint Reader, NFC / RFID Reader, iButton, Light Bar, MSR  |
| <b>Ingress Protection</b>    | IP54 (screen side)   |
| <b>Operating Temperature</b> | 0° C ~ 35° C (32° F ~ 95° F)   |
| <b>Storage Temperature</b>   | -20° C ~ 60° C (-4° F ~ 140° F)  |
| <b>Humidity</b>              | 20% ~ 85% RH non-condensing  |
| <b>W x D x H</b>             | 369 mm x 37 mm x 234 mm (without stand)<br>369 mm x 165 mm x 271.2 mm (with stand)   |
| <b>Weight</b>                | 1.39 kg (without stand)<br>2.25 kg (with stand)  |
| <b>What's in the Box</b>     | Monitor, Stand, 1.8 m USB-C cable, Power supply, NA power cord, EU power cord<br>(Note: power supply required only for HDMI + USB-A connections) |

## MODELOS



### 932PW010100M33

Trek 15.6" Touch Monitor, Stand

Via I. Newton, 4 - 43010 Fontevivo PR - P. IVA: IT02498250345 - TEL: +39 0521 680111 - FAX: - CÓDIGO UNÍVOCO: 8RQN7AZ

As informações técnicas neste site não são vinculadas e podem ser alteradas sem aviso prévio.

Última atualização: 24 abril 2026