



# **TK202III**

# Ticket printer

TK202III is a very fast ticket printer, featuring a printing speed > 200mm/s. Different ticket widths, from 20 to 82.5 mm, easily adjustable by the user. Ticket weight (in grams): from 80 to 255 g/m<sup>2</sup>. 1D and 2D barcode printing.



#### **CARACTERISTICI**

- Ticket printer for heavy workloads
- Printing speed up to 200 mm/s
- Ticket width: from 20 to 82.5 mm
- Ticket weight (in grams): from 70 to 255 g/m<sup>2</sup>
- Improved print head quality for crisp printouts
- Fan-fold / paper roll holder
- Embedded display on 2 lines

#### **FOCUS ON**

- 1D and 2D barcode printing: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, QRCODE
- RS232 + USB interface
- Sensors: fully adjustable lower and upper optical sensor, to suit any ticket width and to detect black marks/gaps
- The tear-off function is the ideal solution to reduce costs, the cutter does not wear even with labels
- Graphics: dynamic logo (graphic memory max 2MB)
- Characters: True Font character support, any language available



# **ACCESORII**

# What is in the box:

• Device, ruler, AC adapter, short guide, reducer for paper width <40mm, serial cable, USB cable, 220V power cable

#### FI?? TEHNIC?

| Printing Method    | Thermal with fixed head   |
|--------------------|---|
| Number of dots     | 8 dots/mm   |
| Resolution         | 203 DPI   |
| Printing (mm/sec)  | >200 mm/sec   |
| Character set      | PC437, PC850, PC860, PC863, PC865, PC858  |
| Printing Format    | Height and width from 1x to 8x, reverse, underlined, italic, bold   |
| Printing Direction | Straight, 90°, 180°, 270°   |
| Paper width        | From 20mm to 82.5mm (2mm step)  |
| Paper weight       | from 70 to 255 g/m <sup>2</sup>   |
| Emulation          | CUSTOM/POS - SVELTA   |
| Interfaces         | RS232 / USB   |
| Data Buffer        | 64 KB   |
| Flash Memory       | 16 MB   |
| Graphic Memory     | Dynamic logo management (graphic memory max 2MB)  |
| Drivers            | Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); OPOS; Android™; iOS |
| Software Tools     | PrinterSet, CustomPowerTool, Status Monitor   |
| Power supply       | 24 Vac ± 10%  |
| Medium consumption | 0.8A (12,5% dots turned on)   |
| Head Life          | 100Km /100M pulses  |
| Dimensions         | 252.1 (L) x 192.6 (H) x 216 (W) mm  |
| Weight             | 4 Kg  |

# **MODELE**





**911BD050100313**PRINTER TK202III USB RS232

Via Berettine, 2 - 43010 Fontevivo PR - TVA: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - COD UNIC: 8RQN7AZ

Datele tehnice de pe acest site nu sunt obligatorii ⊠ pot fi modificate f⊠r⊠vreo notificare. Ultima actualizare: 04 septembrie 2025