



P-RANGER

Mobile Computer

INCREASE THE PRODUCTIVITY WITH P-RANGER AND OFFER AN ADVANCED SERVICE TO YOUR CUSTOMERS

With the handheld computers of P-RANGER family you can improve the touch computing performances of prosumer category. The management of P-RANGER is easy and fast, thanks to Android 7 that offer a new intuitive platform guaranteeing to the user an extraordinary experience. All the business features of P-RANGER improve the abilities of the employees, maximizing the productivity and reducing the time of the operative cycles. Moreover, the devices are reinforced with LTE data module both for close and open environments. Choose P-RANGER to offer an advanced and cost-effective service to your customers!



???????????

- Cradle
- 4 slots cradle
- Vehicle cradle
- Standard battery
- Extended battery: 8000 mAh (with dedicated battery cover)
- Pistol grip
- TP protective tempered glass
- Silicon case protection
- Car charger

????????????? ???? ??????

RP100 / RP300 / RP340

OS	Android 7.0
Camera	Rear 8 Mpx
Display	5" 1280×720 HD DRAGONTRAIL/AGC
CPU	Octa-core MTK6753
Storage ROM+RAM	16 GB + 2 GB
NFC	yes
GSM	B5/850; B8/900; B3/1800; B2/1900
3G WCDMA	B1/2100; B2/1900; B5/850; B8/900; CDMA2000/EVDO 3G:TD/SCDMA
4G LTE	FDD = B1/2100; B3/1800; B7/2600; B20/800; TDD-LTE = B38/B39/B40/B41
Sim Card	Dual SIM card (two Micro-SIM cards + one MicroSD card)
Wi-Fi/Navigation	2.4/5 GHz GPS, BEIDOU, GLONASS
Bluetooth	4.0
1D/2D Scanner	UPC/EAN, Bookland EAN, UCC Coupon Code, ISSN EAN, Code 128, GS1-128, ISBT 128, Code 39, Trioptic Code 39, Code 32, Code 93, Code 11, PDF417, MicroPDF 417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, Maxi Code, Postal Codes, US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal, etc.
Sensors	3D accelerator, E-compass, proximity sensor, light sensor supported
Battery	4000 mAh (8000mAh for RP340-R and RP350-R) as standard; 8000mAh as option (need a battery cover)
USB ports	Type-C
Fingerprint	up to 5 fingerprints stored (for RP340 and RP350 models)
Dimensions and weight	76 mm (W) × 165 mm (H) × 15.60 mm(D) 250 g
Operating temperature	-20° C to 60°C
Drops	122 cm

???????

