



## P3L

Cost-effective thermal receipt printer delivering performance, flexibility, and reliability

The affordable P3L thermal receipt printer is the perfect solution for businesses looking for reliable performance and flexibility. Designed to support existing and new applications with its triple interface design, the P3L supports USB, serial, and ethernet connectivity. Ideal for retail and hospitality, the P3L's 200mm/second print speed ensures quick transactions at the point-of-sale. Built for longevity, it is equipped with a **long-life print head**, an **integrated high performance buzzer** and an **autocutter** and it's versatile thanks to the wall mounting. Engineered utilizing Custom's 30+ years of printing expertise, the P3L is the leader for cost-effective thermal POS printers.



????????????????

- 1. Triple Interface**  
The P3L comes standard with USB, Serial, and Ethernet interfaces for maximum connectivity
- 2. 200mm/s Print Speed**  
With a print speed of 200mm/s, the P3L will save your business time at the checkout
- 3. Cost Effective**  
The easy-to-use P3L is our most cost-effective POS receipt printer and includes both USB and Serial interface cables
- 4. Warranty That Works Harder**  
The P3L includes a standard 3-Year Advanced Exchange Warranty\* with 2-day replacement service, providing a higher level of protection and support from day one.  
\*Available only in the United States
- 5. Compatible with both Android™ and iOS®**  
It supports printing both from Android™ and iOS®, ensuring the maximum compatibility with various operating systems

## MARKETS

- Retail
  - Hospitality
- 

????????????

- 60W 3pin printer power supply P3L
-

????????????? ??????????

<b>Printing Method</b>	Thermal printing, fixed head
<b>Number of dots</b>	8 dots / mm
<b>Resolution</b>	203dpi
<b>Printing (mm/sec)</b>	200mm/s
<b>Buzzer</b>	High performance integrated
<b>Auto-cutter</b>	Cutter life 1.5 million cuts Partial cut
<b>Printing Direction</b>	Normal, 90°, 180°, 270°
<b>Printing Format</b>	Height and width from 1 to 8, bold, reverse, underlined, italic
<b>Character set</b>	Standard font, Extended Chinese GB18030-2000
<b>Supported Barcode</b>	1D: UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, I25, CODABAR, CODE128, CODE11, MSI 2D: PDF417, QRCODE, DATAMATRIX
<b>Paper width</b>	58/80 mm, adjustable with the supplied adapter
<b>Paper weight</b>	from 55 gr to 80 gr
<b>Sensors</b>	Low paper
<b>Emulation</b>	CUSTOM/POS
<b>Interfaces</b>	USB port RS232 serial port Ethernet port Cash drawer port
<b>Drivers</b>	Windows® (32/64 bit) Linux (32/64 bit)
<b>Tool software</b>	PrinterTool
<b>Power supply</b>	External 24 Vdc ± 10%
<b>Medium consumption</b>	2.5A (12,5% dots turned on)
<b>Head Life</b>	150 Km
<b>Operating temperature</b>	0°C + 40°C
<b>Dimensions</b>	145 mm (W) × 195 mm (D) × 150 mm (H)
<b>Weight</b>	1 Kg
<b>Warranty</b>	3-year advanced exchange, 2-day replacement

???????



**911MX010100733**  
 PRINTER P3L 80MM ETH USB  
 RS232 USA

