

TG02H



本機は、電源ケーブルの接続に誤りがないことを確認し、電源ケーブルの両端をしっかりと差し込みます。電源ケーブルの両端をしっかりと差し込み、電源スイッチをONにします。電源スイッチは、前面パネルの右下にあります。電源スイッチをONにした後、ディスプレイに「TG02H」と表示されます。

- 显示屏 分辨率 200dpi
- 显示屏 尺寸 57 英寸
- 显示屏 亮度 > 80 cd/m²
- 显示屏 刷新率 ≥ 90 Hz
- 接口 RS232 或 USB (带 TTL 接口)
- 显示屏 尺寸 57 英寸
- 显示屏 亮度: ≥ 80 cd/m², 显示屏 刷新率 ≥ 90 Hz, 显示屏-显示屏
- 显示屏 12V 或 24V



??????????????

- ?????????? ?????? ?????- ????? 1D/ 2D (QR CODE)
- ?????????? ?????????????????? ??????: ?????? ?????????????? ?????
- ?????????????????????? ?????????? ?????????? ??????????
- ?????????? ??????????????: ?????????? ?????????????????? -20/+ 70°C
- ?????????? ?????????????????? ? ?????????? ??????????????
- ?????????????? ?????????? ??????????????

?????????????

- ?????????????? ??????????????
- ?????????? ??? ?????????????? ??????- ?????
- ?????????????? ??????????????
- ?????????? ?????????????????????????????

?????????????


??? ? ??????????:

- ??????????????, ?????????????? ?????????, ?????????? ?????????, ?????? ??? ?????????????? ?????????? ?????????

?????????? ????????

????? ??????	????????????? ? ?????????????? ?????????
?????????? ?????	8 ?????/??
?????????? ?????????? ? ?????	?? ????????? 24; 32 ? 42 ??????? ?????????? ? ?????????? ?????
??????????	203 dpi
????????? ?????? (??/ ??)	80 ??/? (????????? 50 ??/?)
?????? ?????????	???????????????? (?? ??????????), ??????????, ??????????
????????????????? ?????-????	1D/ 2D QR CODE
?????? ?????????	????????????, ???????/??????? ?? 1 ?? 8, ???????, ?????????????, ?????????????????, ???????
?????????????? ???????	????????, 180°
????????? ???????	57??
????????????? ???????	?? 55 ?? 60 ??/?
????????? ???????	48 ??
????????? ???????	?? 90??
?????????	????????????? ?????????, ?????????????? ???????, ?????? ?????????????????? ???????, ?????- ?????????
?????????	????????????? Escape Command
????????????	RS232 (TTL ?????????), USB, AUX ?????? ??? ????????? ??????
?????? ???????	8 Kb
????- ???????	4 Mb
???????? RAM	512 Kb
?????????????? ???????	2 ?????????? 384x682 ?????
????????	Windows® (32/64 ???) — ??????? ?? ????????? WHQL ? ?????????????????? ??????????; Linux (32/64 ???); ????????????? COM (Linux ??? Windows 32/64 ???); Android™; iOS
????????? ?????????????????? ?????? ?????????????? ?????? ?????????????? ?????? ?????????????? ??????	Pinbase, CustomPowerTool, Custom Windows API
?????????	12 - 24 Vdc ± 10%
C ??????? ?????????????	0.7 A (12Vdc) 0.4 A (24Vdc)
????????? ?????? ?????????????? ??????? 420 000 ?????? (????????????????? ??????)	
????? ??????? ?????????????? ?????????	50??/100M ???????????
????????? ??????????????	-20/+ 70°C
??????????	129(L) x 120(H) x 100(W) ?? (????????? ?????) 126.2(L) x 85.2(H) x 92(W) ?? (????? ? ??????????????)
????	0,33 ?? ??? ??????????? ???????

???????



915HZ010300300
PRINTER TG02H USB RS232

Via I. Newton, 4 - 43010 Fontevivo PR - IT02498250345 - +39 0521 680111 - 8RQN7AZ

24 2026