



## TP5

### All-in-One POS Terminal

With a sleek, stylish and compact design, the TP5 Pro is perfect for even the most confined POS locations. The TP5 Pro features a 14" TruFlat projected capacitive touchscreen, Intel J1900 CPU, and optional integrated receipt printer.



????????????????

## RESILIENT TOUCH DISPLAY

The TP5 features a 14" widescreen LCD with TruFlat projected capacitive (PCAP) multi-touch technology built to take the rigors of heavy everyday use.

## BEAUTIFUL AND FUNCTIONAL

Built on a sturdy aluminum frame, the TP5 delivers a modern look for your business while maintaining a small footprint, saving you valuable counter space.

## INTEGRATED PRINTER (OPTIONAL)

The integrated printer means no external printer cables creating a clean, cable free environment.

## ENVIRONMENTAL RESISTANCE

With a IP54 Ingress Protection Rating, the TP5 was designed to withstand the harshest of environments.

## HIGH PERFORMANCE CPU

Built on Intel's mobile Bay Trail technology, the fanless TP5 is powered by Intel's latest J1900 CPU. Making it fully capable of handling even the most demanding applications.

---

????????????

- Card Reader (MSR)
- 10" Rear Display
- 2-line Rear Display

### What is in the box:

AIO POS Terminal, AC Power Adapter, Driver Disk, RJ45 to DB9 Serial Cable x 1

---

????????????? ??????????

MODEL	ION-TP5E-F	ION-TP5F-F
Processor	Intel® Celeron J1900 2.4GHzQuad Core	
Bezel	TruFlat Bezel	
Chip Set	Processor Integrated	
System Memory	4~8GB DDR3	
Hard Drive	64~128GB Half Slim SSD	
LCD Display	14" (356mm) LED LCD	
Resolution	1366 x 768	
GraphicMemory	Intel Gen7 up to 854MHz	
Electrical	90W/19V	

PORTS	
I/O	4 x USB 3.0 Type A / 1 x USB 2.0 Type A,Front 3 x RJ45 COM3 with 5V/12V Serial 1 x RJ45 LAN 1 x RJ12 Cash Drawer Port

PHYSICAL	
Housing	ABS
Weight	13.2lbs (6Kg)
Dimensions (w/base) (WxDxH)	14.3"x 7.8"x 13.4" (363mm x 197mm x 340mm)
Tilt Angle	0° - 90°
Housing Color	Black and Silver
Capacitive Touch	10 Point

ENVIRONMENTAL	
IP Rating	IP54: Splash Resistant Screen
Operating Temperature	32°F - 95°F (0°C- 35°C)
Humidity	20%- 80%RH non-condensing
Certifications	FCCClass B, CE, LVD, NOM
Supported OS	Windows 7, Windows 8.1, Windows 10
Warranty	3 years

PRINTER SPECIFICATION		
Interface Details	Integrated USB, or Serial	NA
Emulation	ESC/POS Command Compatible	NA
Print Method	Direct Thermal	NA
Printing Speed	6.3"/sec (160 mm/sec)	NA
Print Resolution	180 DPI x 180 DPI	NA
Printing Direction	Unidirectional with Friction Feed	NA
Sensors	Paper End	NA
Reliability	TPH Life 62.14 miles (100KM)	NA

