



# TPTCM60III

XXXXXXXXXX XXXX XXXXXXXX XXXXXXXXXXXXXXX/XXXXXXXXXX XXXXXXXX

- XXXXXXXX XXXXXXXXXX XXXXXXXX XXX 200dpi
- XXXXXXXX XXXXXXXX 60XXX
- XXXXXXXX XXXXXXXX: XXX 63 XXX 80 XXX
- XXXXXXXXXX > 140 XXX/XXXX
- XXXXXXXX XXXXXXXX XXXXXXXX XXX 180XXX (XXX XXXXXXXX XXXXXXXXXX, XXXXXXXXXX)
- XXXXXXXXXX RS232 XXX USB
- XXXXXXXXXXXXXXXXXXXX XXXXXXX: > 1 000 000 XXXXXXXXXX
- XXXXXXXX: XXXXXXXXXXXXXXX XXXXXXXX, XXXXXXXX XXXXXXXX, XXXXXXXX XXXXXXXXXXXXXXX XXXXXXXX, XXXXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXX (XXXX)

## ????????????????

- XXXXXXXXXXXXXXX XXXXXXXX XXXXXXX-XXXXX 1D/ 2D (QRCODE)
- XXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX XXXXXXX: XXXXXXX XXXXXXXXXXXXXXX XXXXXXX
- XXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX
- XXXXXXXX XXXXXXXXXXXXXXX: XXXXXXXXXXXXXXXXXXXXXXX XXXXXXX XXXXXXXX XXXXXXXXXXXXXXX
- XXXXXXXXXXXXXXXXXXXXXXX: XXXXXXX XXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXX
- XXXXXXX XXXXXXXX XXXXXXXXXXXXXXX (LED)
- XXXXXXXX XXXXXXXX DIN
- XXXXXXXX XXXXXXXX cut&drop
- XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXX XXXXXXXX (XXXXXX)

## ????????????

- XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX
- XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXX XXXXXXXXXXXXXXXXXXXXXXX
- XXXXXXXXXXXXXXX XXXXXXXXXX: XXXXXXX, XXXXX, XXXXX, XXXXXXX XXXXXXXX XXXXXXXXXXXXXXX
- XXXXXXXXXXXXXXXXXXXXXXX XXXXXXXX
- XXXXXXXXXXXXXXX XXXX XXXXXXXXXXXXXXX XXXXXXX-XXXXX
- XXXXXXXXXXXXXXX XXXX XXXXXXXXXXXXXXX
- XXXXXXXXXXXXXXX XXXXXXXXXXXXXXX

?????????? ?

????? ?

8 dots /

203 dpi

( /> ) /

( ( ), , )

UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QRCODE

1 8, , , ,

90°, 180°, 270°

60

60 90 /<sup>2</sup>

63 100

160 (90 ( ) )

CUSTOM/POS, TPTCMII

RS232 + USB

16 Kb

1 , 4

RAM 128KB, 8

Windows® (32/64 ) — WHQL ;  
Linux (32/64 );  
COM (Linux Windows 32/64 );  
Android™

Control, Status Monitor, Custom Windows API

24 Vdc ± 10%

1.2A (12.5% )

( )

0.000.000

0°C + 50°C

194,5(L)x80,3(H)x112,4(W) x x

265,5(L)x80,3(H)x115(W) x x

1,2 ( )

1,5 ( )

??????

