



## KPM302III

RFID

OEM

- 2000 (300 dpi???)
- 20 82.5
- > 200 /
- 1D 2D : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QR CODE
- True Font, .
- , RS232 USB
- : 1.500.000
- : 4 /



??

- RFID : SAM
- 32 bit
- SD 2GB
- ???) (

??:

- : ATB
- 

??:



PrinterS??et

- True Font )
- DLL
- Win XP/Vista /7 / 8/ 10 (+64bit )
- Linux (c.u.ps.)32/64 bit
- MACOSX (c.u.p.s.)
- opos java .net
- Sw EasyMyfare / tag mifare
- Sw EthLocator
- CustomPowerTool

???:

- ( )
- Triple Feeder Stock 3 3
- VeriPrint® ;
- RFID UltraLight, Mifare I- code; RFID ISO 14443 A/B/B'; ISO 14444, Felica, ISO18092 (NFC), Mifare; RFID UHF EPC Gen2;
- / /

??

?????????


- 40mm CUT DROP BURSTER

????

????

	8 /
	203 dpi
	/ 200 / ( ), 170 / ( ), 110 / ( )
	PC437, PC850, PC860, PC863, PC865, PC858
	1 8
	, 90°, 180°, 270°
	54 82.5 (2 )
	80 255 / <sup>2</sup>
	300
	CUSTOM/POS - CUSTOM/LABEL
	RS232 / USB /
	32 KB
	16 MB
	( 1MB )
	Win XP/Vista /7 / 8/ 10 (+64bit ); Linux 32/64 bit ; OPOS, MACOSX
	PrinterSet; CustomPowerTool, EasyMyfare, EthLocator
	24 Vdc ± 10% ( )
	0.8A (12,5% )
MTBF	550,000 ( )
	100 / 100M
MCBF	1.500.000
	0°C + 50°C
	191x123(h)x160
	3.5

??



**915AV210100700**  
 PRINTER KPM302III ETH USB  
 RS232