




PLUS4

4"

PLUS4 4" - 112

80 82.5 PLUS4

4MB



??

- 104
- linerless Maxstick B
- 4MB
- : PDF417 QR
- : GB18030
- LED
- FEED
- ECO :
- :RS232/TTL (), USB
- : , , ()
- UL, CE, FCC, CCC
- 5-8Vdc
- AV05



" " Maxstick B


??

-

????

- RS232/TTL USB, 5-8Vdc
- ()

??



- RS232 DB9 USB 25 9-40VDC

?????????

-
-

????

????

	8 dots/mm
	46 (11cpi) 59 (15cpi) 83 (20cpi)
	203 dpi
/	50, 70 mm/sec
	(GB18030)
	PDF417 QR
	112 (114) 80 82.5
	50-60 g/m ²
	104mm
	50mm 12mm
	Escape Command , PlusII
	RS232/TTL, miniUSB,
	2kB
	4MB
	1MB +4MB 128KB + 8MB RAM
	Windows® 32/64 --- WHQL
	Linux 32/64
	COM Linux Windows 32/64
	™
	iOS
	PrinterSet, CustomPowerTool, Status Monitor, Custom Windows API
	5-8 Vdc
MTBF	180.000 ()
	50 / 100 MI
	-10 a +60
	UL, CE, FCC, CCC
	149(L) x 97,8(H) x 71,7(W) 89,1(W)
	390 (510)

??



915GJ010100322

PRINTER PLUS4 USB RS232 TTL

Via I. Newton, 4 - 43010 Fontevivo PR -

IT02498250345 -

+39 0521 680111 -

- 8RQN7AZ

18 2026