



## TL60III

/ 60

- /
- 200 dpi
- 60
- : 63 85 mm
- > 140 /
- RS232 USB
- : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- :
- : 1.000.000
- :

??

- : 77
- , -20°C +70°C
- :
- 80
- 

??:

- Kiosk
- 

??:

- PrinterSet
- CustomPowerTool

??

?????????

-

????

????

	8 /
	24 - 32 - 44
	203 dpi
	/ 140 /
	PC437, PC850. PC860. PC863, PC865, PC858, PC866, VISCI( 0104:PC437, PC850. PC860. PC863, PC865, PC858, GB2312)
	1 4
	, 180°
	60
	55 80 / 2
	63 85
	80
	Custom/POS, TGH
	RS232 + USB
	2 kB
	1 MB
	2 448x584
	Windows, Linux
	Status Monitor, PrinterSet, CustomPowerTool
	24V +/- 10%
	0.65A (12,5% )
MTBF	172.000 ( )
	50 /100M
MCBF	1.000.000
	-20°C + 70°C
	130(l)x105(w)x77(h)
	0.800

??



**915CJ020100300**  
PRINTER TL60III USB RS232



**915CJ020200300**  
PRINTER TL60III USB RS232  
EJECTOR

