



TL60III

/ 60

- /
- 200 dpi
- 60
- : 63 85 mm
- > 140 /
- RS232 USB
- : UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QR CODE
- :
- : 1.000.000
- :



??

- : 77
- , -20°C +70°C
- :
- 80
-

??

- Kiosk
-

??

?????????

•

????

????

8 /

24 - 32 - 44

203 dpi

/ 140 /

PC437, PC850. PC860. PC863, PC865, PC858, PC866, VISCII(0104:PC437, PC850. PC860. PC863, PC865, PC858, GB2312)

1 4

, 180°

60

55 80 / ²

63 85

80

Custom/POS, TGH

RS232 + USB

2 kB

1 MB

2 448x584

Windows® 32/64 — WHQL

Linux 32/64

COM Linux Windows 32/64

™

Status Monitor, PrinterSet, CustomPowerTool, Custom Windows API

24V +/- 10%

0.65A (12,5%)

MTBF 172.000 ()

50 /100M

TL60III /

TL60III EJ

-20°C + 70°C

130(l)x105(w)x77(h)

0.800

??



915CJ040100300

PRINTER TL60III USB RS232



915CJ040200300

PRINTER TL60III USB RS232
EJECTOR

Via I. Newton, 4 - 43010 Fontevivo PR -

IT02498250345 -

+39 0521 680111 -

- 8RQN7AZ

12 2026